


## TUBULAR LEVEL GAGE


### MODEL



### TLA-S




### TLA-F



### TLB-F



### TLA-F 二段式



### DIMENSIONS m/m

MODEL	C	H	段數
TL-03	300	200	1
TL-05	500	400	1
TL-08	800	700	1
TL-10	1000	900	1
TL-12	1200	1100	1
TL-15	1500	1400	1
TL-18	1800	1700	1
TL-20	2000	1900	1
TL-22	2200	2100	2
TL-25	2500	2400	2
TL-28	2800	2700	2
TL-30	3000	2900	2


### TLAP-F



### TLBP-F



### TLAV-F



### TLBV-F



### SPECIFICATIONS

MODEL	BODY	TUBE	SEAL	VALVE	BALL CHECK	CONN.	TEMP.	PRESS.	PROTECT
TLA-F 不銹鋼堅固型法蘭口	304SS	GLASS	NEOPRENE	NEEDLE VALVE	WITH OR NOT	1/2"~1" PT,NPT JIS ANSI DIN FLANGE	MAX. 200°C	MAX. 7 Kg/cm <sup>2</sup>	304SS
TLA-S 不銹鋼緊密型牙口	316SS	P.V.C	VITON	VALVE	NOT	1/2"~1" PT,NPT JIS ANSI DIN FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS
TLB-F 不銹鋼簡單型法蘭口	316LSS	P.V.C	TEFLON	VALVE	NOT	1/2"~1" PT,NPT JIS ANSI DIN FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS
TLB-S 不銹鋼簡單型牙口	PP	P.V.C	VITON	VALVE	NOT	1/2"~1" PT,NPT JIS ANSI DIN FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS
TLAP-F 塑膠堅固型法蘭口	P.V.C	GLASS	NEOPRENE	NEEDLE VALVE	WITH OR NOT	1/2"~1" PT,NPT JIS ANSI DIN FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS
TLAP-S 塑膠緊密型牙口	PP	P.V.C	VITON	VALVE	NOT	1/2"~1" PT,NPT JIS ANSI DIN FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS
TLBP-F 塑膠簡單型法蘭口	PVDF	P.V.C	TEFLON	VALVE	NOT	1/2"~1" PT,NPT JIS ANSI DIN FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS
TLBP-S 塑膠簡單型牙口	PP	P.V.C	TEFLON	VALVE	NOT	1/2"~1" PT,NPT JIS ANSI DIN FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS
TLAV-F 塑膠堅固型法蘭口	PP	GLASS	VITON	GLOBE VALVE	NOT	1/2" JIS10K FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS
TLBV-F 塑膠簡單型法蘭口	P.V.C	P.V.C	TEFLON	VALVE	NOT	1/2" JIS10K FLANGE	MAX. 60°C	MAX. 4 Kg/cm <sup>2</sup>	304SS

Note: LEVEL SWITCH: READ SWITCH(磁簧開關) CAPACITIVE PROXIMITY SENSORS(靜電容近接開關)

歡迎訂製各式管狀式液面計，敬請惠予告知下列之條件：

1. 型式 (Model)      2. 液體名稱 (Name of liquid)      3. 材質 (Material)      4. 接續方式 (Connection)  
5. 操作壓力 (Oper Pressure)      6. 操作溫度 (Oper temp)      7. 尺寸C,H (Size (C,H))

### SYNTEX TECH CORP.

NO.503,SEC.2,JINLING RD.,PINGJHEN CITY,TAOYUAN COUNTY 324,TAIWAN,(R.O.C)

TEL:886-3-4679659 FAX:886-3-4679649

www.syntextech.com.tw    syntex.tech@msa.hinet.net